

Air-G **CLEAR LENS**





Features

- ▲ Certified medium impact rated protection to AS/NZS 1337.1:2010
- ▶ Diamond Tech Hardcoat provides extreme scratch resistance and resists acid and solvent degradation
- HydroTech AF is a washable hydrophilic based coating providing an anti-static finish that repels dusts and particles and prevents fog forming on the lens, the ideal coating for hot and humid conditions
- Base 9.5 curve provides excellent optical clarity and an extended wrap for increased side protection
- ▲ Force360's Element Seal provides protection from dust and harsh winds
- Element Seal can be removed if not in use
- UV400 Polycarbonate lenses offer the wearer the best protection against UVA and UVB damaging rays
- Ultra thin lenses provide outstanding optical clarity
- ▲ Made from 100% durable and resilient polycarbonate
- Connection point for spec cord or lanvard
- ▶ Universal nose bridge that suits most faces

Standards & Certification

Force360 recognise that without product certification by a Notified Body all product performance testing, and adherence to standards claims cannot be independently verified.

If they are not as claimed, serious safety implications for the wearer, and legal implications for the supplier and even the employer may arise.

Force360 source their entire range of FPR eye protection from a single manufacturing partner to ensure consistency and reliability of product, but most importantly Force360 have taken the further step of engaging a globally recognised Notified Body to audit and certify both the manufacturing

All of Force360's eye protection is certified to the latest AS/NZS eye protection standards.



Specfications

Part No. EFPR800G **Lens Colour** Clear Lens **VLT Rating** 89% Lens Shade Category 0

Packaging

1 🗍 12 🔊 144 🛞





EFPR800G

Key Technologies



Medium Impact

Certified medium impact rated protection to AS/NZS 1337.1:2010.



Diamond Tech HardCoat

Force360 uses its own Diamond Tech Hardcoat on all FPR lenses. Diamond Tech Hardcoat is extremely scratch resistant and resists acid and solvent degradation as well as scratches from dusts and debris.



HydroTech AF

Force360 uses its HydroTech Anti Fog coating on most FPR safety lenses. HydroTech AF is a washable hydrophilic based coating providing an anti static finish that repels dusts and particles and prevents fog forming on the lens, the ideal coating for hot and humid conditions.



Element Seal

Force360's Element Seal provides protection from dust and harsh winds that can compromise standard safety spectacles. The Element Seal is made from high quality EVA ensuring a soft and positive seal on the skin.



UV400

UV400 Polycarbonate lenses offer the wearer the best protection against UVA and UVB damaging rays. 100% protection is the standard across the entire Force360 FPR eyewear range.

Radiation Guide

UVA/UVB 280-380nm	UV light rays from the sun are invisible to the eye yet can cause serious damage including corneal blistering, cataracts, premature aging, conjunctivitis and partial blindness						
Visible Light 380-780nm	Intense visual bright light can cause retina damage and create visual perception issues						
Blue Light 380-500nm	Blue light rays from the sun or artificial lighting like neons, cause eye strain and fatigue. Colours and definition can be adversely affected. In extreme cases blindness can occur						
Infra Red Light 780-1400nm	Infra Red rays from the sun or mechanically heat generating applications like gas welding can cause eye dryness and corneal damage, macular degeneration and blindness						

Range Specifications

Force360 Code	Product Name	Lens Type	Temple Colours	Coating	OC Category	Lens Markings	UV Light Absorption: 280-380NM	Visible Light Transmission: 380-780NM	Blue Light Absorption: 380-500NM	Infrared Light Absorption: 780NM- 1400NM
EFPR800G	Air-G	clear	clear	AF/HC	0	100	100%	89%	12%	9.76%
EFPR801G	Air-G	smoke	smoke	AF/HC	2	12	100%	23%	77%	46.84%

Eyewear Care

Force360 recommends eyewear is cleaned using Force360's exclusive FogOff non alcohol spec wipe.
Part number EFPR950.

Weight

